

Accepted Programs

Files created with current versions of (Mac or PC):

- InDesign
- Illustrator
- Photoshop
- Corel Draw - convert type to curves

NOT Accepted

Files created with:

- Microsoft Publisher
- Microsoft Powerpoint
- Microsoft Word
- PageMaker: convert to InDesign

Pre-Design Checklist

Page Layout: before starting your design, download item template from foldersolutions.com

- ☐ for custom items, call us first; we will create a template to your specs *before* you begin your artwork.

.PDF File Artwork:

Wrong template, missing bleed, low-quality graphics will be rejected.

- ☐ high-resolution (print quality) .PDF documents, including 1/8" bleed

Layout Files & Elements:


- ☐ use "package" function in program to collect all elements used in file, including: fonts, graphics, logos, scans, etc.
- ☐ vector art: convert type to outlines save as **.EPS**
- ☐ images (photos): 300 dpi high-res CMYK & grayscale save as **.PSD** or **.TIF**
- ☐ scans: 1200 dpi, bitmap format save as **.PSD** or **.TIF**
- ☐ colors: use CMYK or spot/PMS **not RGB**
- ☐ **not acceptable: RGB low resolution (72 dpi) web graphics**


Ink Colors:

- ☐ spot color PMS (Pantone®) printing: use **SPOT/PMS** colors
- ☐ four color process (full color) printing: use **CMYK - NOT RGB**
 - ☐ for large black areas (not type), we suggest the following rich-black mix: cyan 60% magenta 40% yellow 40% black 100%
 - ☐ avoid "Blues that look Purple" refer to the Pantone® Formula Guide and/or Pantone® Color Bridge (www.Pantone.com)
 - ☐ choose a blue formula with 30% more cyan than magenta

Foil Stamp & Emboss:

- ☐ supply one color vector (.EPS) art: convert type to outlines

EMBOSS: thick, bold copy is better. Recommended minimum line thickness is 2 PT.  Increase point size/line weight accordingly. Certain copy will not emboss well and should be avoided: serif/thick-thin type, screens, fine lines and copy with intricate detail.

FOIL STAMP: for most type styles, minimum point size is 8 PT. Increase size for serif/thick-thin styles. To avoid loss of detail and plugging do not use ultra-light type styles, screens, thin lines and copy with intricate detail and gaps no closer than 1 pt. 

Avoid Errors & Job Delays:

- ☐ Proofread & test print your files: print color separations; print a reduced, cut-out & fold up...does copy fall on correct panels? Additional charges apply if we need to modify your files. **We are not responsible for errors in supplied files.**

Sending Art Files

1 Ensure artwork & layout matches specs quoted...

- Follow Pre-Design Checklist

2 Compress files (.zip) before sending

3 Email or Upload Files

- include dealer P.O. number and job name in the subject line
- send dealer P.O. with art files
- reference Quote number

Email SMALL files (under 10 MB)

Upload LARGE files:

go to: FolderSolutions.com
select: Help Center
choose: Art Upload